

chemical solutions to concrete problems

CLEAR PRE-FORM

CONCRETE FORM SEALER



PROTECT WOOD FROM CONCRETE **ALKALIS**



ELIMINATES WOOD TANNIN AND WOOD **SUGAR MIGRATION**



TACK-FREE IN 15 MINUTES



EASY APPLICATION



BENEFITS

- Uniform Concrete Finish: Promotes color uniformity and density
- Universal Application: Clear-Pre Form can be used on most lumber and engineered wood surfaces, including MDF, particleboard, OSB, non-overlaid plywood, and paint-grade MDO
- Ideal for Board Form Finish: Reduces rough, porous, and dusty concrete caused by wood sugars in plywood and rough sawn dimensional lumber
- Grain Coverage: Multiple coats mask wood grain texture
- Rapid Cure: Dries tack-free in 15 minutes at 70°F for outdoor and formwork use
- High-Strength Bond: Penetrates wood and chemically reacts with cellulose to form a high-strength bond that seals wood forms
- Ready-to-Use: Requires no dilution







Clear Pre-Form is a solvent based, transparent, polyurethane sealer for protecting most wood surfaces. It works by reducing water absorption into the wood, thus minimizing the migration of dissolved wood sugars and tannins into the concrete. Resulting concrete surfaces are typically uniform in color and free of dusting caused by wood sugar retardation.

APPLICATIONS

- Product can be sprayed, rolled, or brushed
- Use in single coat applications to preserve the natural texture of rough sawn or embossed boards/panels
- Where a smooth, glossy, grain-free surface is required, multiple coats, with sanding in between, may be necessary
- Best results are obtained when a Nox-Crete release agent is used in combination with Clear Pre-Form

PACKAGING

• 5 gallon (19 L) pails



SCAN FOR INFO

FOLLOW US







