



chemical solutions to concrete problems

# PERFECT SPRAYER



## COMMERCIAL-GRADE SPRAYER

Specifically designed for light, consistent application of concrete form release agents

## FEATURES

- 3.4 gal. (12.9L) Tank with 2.75 gal (10.4L) fill capacity
- Heavy-duty stainless steel tank with an external hammered coating finish that resists corrosion and chemical degradation
- Built-In pressure gauge for monitoring tank pressure
- Maximum pressure of 116psi (8 bar / 800 kpa)
- Can be pressurized using hand pump or air compressor fill valve
- Tank equipped with pressure relief valve to prevent overcharging
- Includes 5ft. (152cm) of chemical resistant hose that remains flexible even in below freezing conditions
- Utilizes a heavy-duty, pistol grip shut-off that is designed for comfort and long-term durability under extreme conditions
- Incorporates a heavy-duty stainless steel wand made from pipe that won't bend like traditional spray wands made from brass or plastic tube
- Swivel fitting from hose to shut-off



[nox-crete.com](http://nox-crete.com) • 402-341-2080

FOLLOW US



# FEATURES

- Includes two backpack-style carrying straps that helps free up the hands of the sprayer operator
- Includes a wide funnel-style opening to reduce spills during filling of sprayer
- Pump includes a funnel cover to prevent dirt and debris from collecting in the fill area where it can ultimately end up in the tank
- Wide base prevents sprayer from falling over and includes a convenient storage area for spray wand
- Includes a 100 mesh filter located immediately behind the spray tip



## OPTIONAL EQUIPMENT

- Extra spray tips in various sizes ranging from 0.67-1.0 GPM
- Pressure Regulator
- 40psi pressure-regulating non-dripping control flow valve
- 50 mesh filter for larger optional tip sizes

**CF Valve 40psi**



**Pressure Regulator**



**Extra Spray Tips**



For more information, review the sprayer manual. Sprayer parts available from Nox-Crete.