

SELECT JOINT TAPE

A specialized polyethylene tape for tilt-up construction, applied as a temporary saw-cut joint cover.

HOW IT WORKS

Select Joint Tape is a UV-resistant polyethylene tape to be used as a temporary cover for saw-cut joints on tilt-up casting slabs to prevent concrete and debris intrusion. Select Joint Tape has excellent adherence to properly prepared concrete and leaves no residue on the casting slab when removed. Select Joint Tape may be applied either before or after application of Nox-Crete's Silcoseal water-based bondbreakers. Select Joint Tape will greatly reduce or eliminate rubbing and patching of the panel face when compared to traditional methods.

APPLICATIONS

- ◆ Use to cover saw-cut joints or other imperfections on tilt-up casting slabs to prevent concrete and other debris from entering and transferring to the panel face.

ADVANTAGES

- ◆ Forms a tight seal to prevent concrete, dust, and debris from entering saw-cut joint.
- ◆ Leaves no adhesive residue on casting slab.
- ◆ Greatly reduces or eliminates rubbing and patching of wall panel surface.
- ◆ Resistant to UV degradation for up to 28 days.
- ◆ Waterproof.
- ◆ Resistant to Nox-Crete **water-based** bondbreakers.
- ◆ Resistant to submersion for up to 48 hours.

⚠ PRECAUTIONS ⚠

- ◆ Not for use in conjunction with **solvent-based** bondbreakers.
- ◆ Do not use if tape or concrete surface temperature is below 40°F (4°C) or above 140°F. (60°C)
- ◆ Do not apply to surfaces that are wet.
- ◆ When applied over a cure coat of Silcoseal bondbreaker, the bondbreaker should be allowed to dry completely prior to application of Select Joint Tape.
- ◆ Application of Silcoseal bondbreakers over Select Joint Tape may cause some slight discoloration of the tape, but will not affect performance.
- ◆ Due to the differential in curing, the casting/floor slab may show signs of shadowing when tape is removed. This effect is minimal and will fade over time.

USE INSTRUCTIONS

- ◆ Verify casting slab surface is dry and clean of dirt, sand, cement dust or other surface contaminants.
- ◆ Verify casting slab surface is within the recommended temperature range.
- ◆ Verify a maximum of one coat of Silcoseal bondbreaker has been previously applied. If additional coats of Silcoseal have been applied it may be necessary to remove excess bondbreaker to ensure adequate adhesion.
- ◆ Apply tape so that an even amount is on either side of the joint. Use feet or roller applicator to make sure that the tape is fully adhered to the slab.

PACKAGING

Product is sold by the case, 24 rolls/case. Each roll is 2 in (5 cm) wide x 60 yds (55 m).

SHELF LIFE

Shelf life is two years from the date of manufacture. Use before the "USE BY" date stated on product packaging.

HANDLING/STORAGE

Store in a cool, dry location, away from direct sunlight within a temperature range between 32° F (0° C) and 100° F (38° C). Keep tape in original packaging for as long as possible.

AVAILABILITY & TECHNICAL SERVICES

In addition to corporate offices in Omaha, Nebraska, NOX-CRETE, INC., maintains regional offices and distribution centers in principal markets throughout the world. For source or technical information, call 800-669-2738 or 402-341-2080.

LIMITED WARRANTY

NOTICE-READ CAREFULLY CONDITIONS OF SALE

NOX-CRETE offers this product for sale subject to, and Buyer and all users are deemed to have accepted, the following conditions of sale and limited warranty which may only be varied by written agreement of a duly authorized corporate officer of NOX-CRETE. No other representative of or for NOX-CRETE is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

NOX-CRETE warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, NOX-CRETE will replace the defective product with new product without charge to the purchaser.

NOX-CRETE makes NO OTHER WARRANTY, either express or implied, concerning this product. There is NO WARRANTY OF MERCHANTABILITY. In no case shall NOX-CRETE be liable for special, indirect or consequential damages resulting from the use or handling of the product and no claim of any kind shall be greater in amount than the purchase price of the product in respect of which damages are claimed.

INHERENT RISKS

NOX-CRETE MAKES NO WARRANTY WITH RESPECT TO THE PERFORMANCE OF THE PRODUCT AFTER IT IS APPLIED BY THE PURCHASER, AND PURCHASER ASSUMES ALL RISKS ASSOCIATED WITH THE USE OR APPLICATION OF THE PRODUCT.

nox-crete®

chemical solutions to concrete problems